



Rohrdurchmesser- und Rundheitstoleranz nach DIN EN 10296-1
 Die Artikel-Nr. bezieht sich auf pulverbeschichtete Ausführung.

Rohr	Ø 60		Ø 80		Ø 100		Ø 120		Ø 140	
Artikel-Nr.	11061240	-	11081240	-	11101240	-	11121240	-	11141240	-
Ø d	57		77		100		120		136	
Ø D	72		92		115		135		151	
B	60		70		100		110		120	
L	130		150		200		220		240	
S	1,5	-	1,5	-	1,5	-	1,5	-	1,5	-
Gewicht in kg	0,55	-	0,60	-	1,00	-	1,20	-	1,40	-
Rohr	Ø 150		Ø 175		Ø 200		Ø 224		Ø 250	
Artikel-Nr.	11151240	-	11171240	-	11201240	-	11221240	-	11251240	-
Ø d	150		175		200		220		250	
Ø D	165		190		215		235		265	
B	125		137,5		150		162,5		175	
L	250		275		300		325		350	
S	1,5	-	1,5	-	1,5	-	1,5	-	1,5	-
Gewicht in kg	1,65	-	2,05	-	2,55	-	2,90	-	3,50	-
Rohr	Ø 280		Ø 300		Ø 315		Ø 350		Ø 400	
Artikel-Nr.	11281240	-	11301240	-	11311240	-	11351240	-	11401240	-
Ø d	277		300		312		350		399	
Ø D	292		315		327		365		414	
B	190		200		210		275		300	
L	380		400		420		550		600	
S	1,5	-	1,5	-	1,5	-	1,5	-	1,5	-
Gewicht in kg	4,30	-	4,70	-	5,30	-	8,10	-	9,90	-
Rohr	Ø 450		Ø 500		Ø 560		Ø 630		Ø	
Artikel-Nr.	11451240	-	11501240	-	-	12561240	-	12631240	-	-
Ø d	449		499		558		628		-	
Ø D	464		514		574		644		-	
B	325		350		380		415		-	
L	650		700		760		830		-	
S	1,5	-	1,5	-	-	2	-	2	-	-
Gewicht in kg	12,75	-	14,10	-	-	22,15	-	26,80	-	-

Benennung:

T-Stücke

Datum: 05/14

Maßblatt-Nr. 5/1

Rev. 1